

Examples

Send SMS

Example webservice URL:

```
“ http://infopi.io/text/index.php?app=ws&u=<username>&h=<token>&op=pv&to=09876
```

Explanation

operation `pv` (send SMS) was accessed by a user using username `u` and webservises token `h` with destination number `to` 0987654321, message `msg` 'test only' and expected output format is the default format, JSON format.

When successful InfoPi will returns OK status message in JSON format:

```
{"data":[{"status":"OK","error":"0","smslog_id":"30","queue":"afb5f34575e30ec4efe4471cf5d1bee4null}]}
```

If error occurred Infopi returns one of the return code, also in JSON format.

List of incoming SMS

Example webservice URL:

```
“ http://infopi.io/text/index.php?app=ws&u=<username>&h=<token>&op=in&kwd=scho
```

Explanation:

InfoPi webservices in infopi.io with operation `in` (incoming SMS) was accessed by a user using username `u` and webservises token `h` with keyword `kwd` school and expected output format is in XML format `format=xml`.

When successful InfoPi will return OK status message in XML format:

```
<response>
```

```
  <data>
```

```
    <item>
```

```
      <id>2</id>
```

```
      <src>+254987654321</src>
```

```
<dst>1234</dst>

<kwd>school</kwd>

<msg>A</msg>

<dt>2013-05-20 12:40:38</dt>

<status>1</status>

</item>

</data>

</response>
```

If error occurs InfoPi will return one of the error codes, also in XML format.

List of Contacts on Phonebook

Example webservice URL:

```
“ http://infopi.io/text/index.php?app=ws&u=<username>&h=<token>&op=get_contact&h
```

Explanation:

Infopi webservices in infopi.io with operation `op` `get_contact` was accessed by a user using username `u` and webservices token `h` with keyword `kwd` `james` and expected output format is in JSON format.

When successful InfoPi will return OK status message in JSON format:

```
{ "status": "OK", "error": "0", "data": [ { "pid": "1234", "gp_id": "2", "p_desc": "James Doe", "p_num": "08901230659", "email": "", "group_name": "Test Group", "code": "TESTGROUP" } ], "multi": true }
```

If error occurred InfoPi will returns one of the return code, also in JSON format.

Revision #4

Created 3 October 2016 13:29:42 by mwaurahmn

Updated 10 October 2016 11:14:29 by mwaurahmn